

YÜK KALDIRMA MIKNATISI / LIFTING MAGNET

| | LD 01 | LD 03 | LD 06 | LD 10 | LD 20 | LD 30 | LD 50 | |
|---|-------|-------|-------|-------|-------|-------|-------|----|
| Çalışma yük limitleri / Working load limits | 100 | 300 | 600 | 1000 | 2000 | 3000 | 5000 | kg |
| Kantlanmış test yükü / Proof test load | 350 | 1050 | 2100 | 3500 | 6000 | 9000 | 15000 | kg |
| Uzunluk / Length (L) | 100 | 175 | 225 | 280 | 360 | 435 | 540 | mm |
| Genişlik / Width (B) | 82 | 105 | 140 | 160 | 210 | 286 | 316 | mm |
| Yükseklik / Height (H) | 80 | 100 | 125 | 155 | 185 | 245 | 295 | mm |
| Ağırlık / Weight | 5.5 | 11.5 | 26.5 | 48 | 80 | 180 | 380 | kg |

| | |
|------------------|----------|
| Art.No. 52000153 | NL-LD 01 |
| Art.No. 52000154 | NL-LD 03 |
| Art.No. 52000155 | NL-LD 06 |
| Art.No. 52000156 | NL-LD 10 |
| Art.No. 52000157 | NL-LD 20 |
| Art.No. 52000158 | NL-LD 30 |
| Art.No. 52000159 | NL-LD 50 |

| | Çelik kalınlığı/ Thickness of Steel | | Kapasite oranı/ Capacity rate | | | | | |
|-----|--|------------|-------------------------------|-------|-------|-------|-------|-------|
| | mm | inch | LD 30 | LD 20 | LD 10 | LD 06 | LD 03 | LD 01 |
| T1 | Up to 60 | Up to 2.36 | 100% | 100% | 100% | 100% | 100% | 100% |
| T2 | 55 | 2.16 | 95% | | | | | |
| T3 | 50 | 1.97 | 90% | 95% | 100% | 100% | 100% | 100% |
| T4 | 45 | 1.77 | 85% | 90% | | | | |
| T5 | 40 | 1.57 | 80% | 85% | 100% | 100% | 100% | 100% |
| T6 | 35 | 1.38 | 70% | 75% | | | | |
| T7 | 30 | 1.18 | 60% | 65% | 80% | 100% | 100% | 100% |
| T8 | 25 | 0.98 | 50% | 55% | 70% | | | |
| T9 | 20 | 0.79 | 40% | 45% | 60% | 75% | 90% | 100% |
| T10 | 15 | 0.59 | 30% | 35% | 50% | 60% | 70% | |
| T11 | 10 | 0.39 | 20% | 25% | 35% | 45% | 50% | 70% |
| T12 | 5 | 0.20 | 10% | 15% | 20% | 25% | 30% | 40% |

